



SVERO

## CHAIN HOIST, 14, 500KG, OP, LH:3,0M

Art nr.1412900

500 kg chain hoist with overload protection is suitable for lifting in many situations. An all-round chain hoist from Svero for, for example, the smaller workshop or pump station.

### Description

- with built-in overload protection
- can be ordered with adapted lifting and/or operating height
- fits most beam trolleys and beam clamps
- 0.5-20 tons can be obtained with overload protection
- powder-coated housing in steel provides very good rust protection
- swivelling hooks with safety latch
- safe, well protected, automatic load pressure brake
- load chain treated with COROLIM® provides excellent corrosion protection
- double layers on the chain link ensure perfect balance and smooth running
- working temperature -10° C up to +50° C
- traceable with unique SVERO serial number
- each chain hoist is dynamically test loaded with 1.5 x WLL before leaving production
- test and CE certificates and manual included

### Specifications

|                         |             |
|-------------------------|-------------|
| Art nr.                 | 1412900     |
| WLL                     | 500 kg      |
| Test Load               | 750         |
| Security ratio          | 4:1         |
| Standard lift           | 3 m         |
| Load chain              | 5 X 15      |
| Falls                   | 1           |
| Standard maneuver chain | 3 m         |
| Hand chain              | 5 X 23.7 mm |
| Weight, net             | 9.0 kg      |
| Marking                 | CE, WLL     |
| Standard                | SS-EN 13157 |
| Brand                   | SVERO       |