## SVERO



SVFRO

## Chain Hoist 5000 kg, lift 3 m, manual

Art nr.1419

Chain hoist 5000 kg from Svero for really heavy lifting in, for example, the process industry and energy generation.

## Description

- can be ordered with adapted lifting and/or operating height
- fits most beam trollies and beam clamps
- 0.5-20 tons can be obtained with overload protection
- powder-coated housing in steel provides very good rust protection
- swivelling hooks with safety latch
- safe, well protected, automatic load pressure brake
- load chain treated with COROLIM® provides excellent corrosion protection
- double layers on the chain link ensure perfect balance and smooth
- working temperature -10° C up to +50° C
- traceable with unique SVERO serial number
- each chain hoist is dynamically test loaded with 1.5 x WLL before leaving production
- test and CE certificates and manual included

## Specifications

Art nr.	1419
WLL	5000 kg
Test Load	7500
Security ratio	4:1
Standard lift	3 m
Load chain	9 X 27
Falls	2
Standard maneuver chain	3 m
Hand chain	5 X 23,7 mm
Weight, net	36.6 kg
Marking	CE, WLL
Standard	SS-EN 13157
Brand	SVERO

Momarken 19, 556 50 Jönköping +46 36 316570 | info@svero.com