



SVERO

## Integrated low-build chain hoist/trolley 500 kg

Art nr.2712

SVERO 27 is a low-built beam trolley with an integrated chain hoist. From the underside of the beam to the load position, the distance, depending on capacity, is only 235-275 mm. Available with adapted lifting height.

### Description

- low headroom
- adjustable for IPE, HEA, HEB or INP beams
- powder-coated steel sides
- width is adjusted with spacers
- rubber shock absorbers
- test loaded with 1.5 x WLL
- safety factor 4:1
- working temperature -10° C up to +50° C
- test and CE certificates and manuals included
- traceable with unique SVERO serial number

### Specifications

|                         |                     |
|-------------------------|---------------------|
| Art nr.                 | 2712                |
| Standard maneuver chain | 3 m                 |
| Weight, net             | 10.0 kg             |
| Standard lift           | 3 m                 |
| Security ratio          | 4:1                 |
| Marking                 | CE, WLL, BEAM WIDTH |
| Headroom (Hmin)         | 244                 |
| Load chain              | 5 X 15              |
| Hand chain              | 5 X 23,7 mm         |
| WLL                     | 500 kg              |
| Beam width              | 51-203              |
| Test Load               | 750                 |
| Standard                | SS-EN 13157         |
| Brand                   | SVERO               |

