

HUCHEZ

PRIMO Winch 500KG, 1- phase

Art nr. 1PRIMO501BT

Electric winch 500 kg. Economical range subject to the same quality standard as the TRBoxter range.

Use:

- Simple lifting and pulling/hauling operations
- Intermediate operating factor
- Boat hauling
- Lifting doors, hatches
- Freight lifts
- Traps opening
- Theatre applications
- Swimming pool roofs

Description

- Steel rigid structure.
- Mechanical welded steel drum with flanges allowing a secure fastening of the wire rope.
- Mechanical parts machined and protected by cataphoresis.
- Single phase 230 V motor brake with permanent capacitor - 50 Hz lifting type. P = 1.1 kW. Class F. IP 54 Protection.
- Low voltage control assuring user protection against electric risks.
- Up-down pendant control with emergency stop, cable 3 m long.
- Reducer in oil bath with helical gears.
- Limit switch as standard, very easy to adjust and extremely reliable.
- Options: rope-press roller and grooved drum.

Specifications

| | |
|------------------------|-------------|
| Art nr. | 1PRIMO501BT |
| WLL | 500 kg |
| Wire diameter | 7 mm |
| Max wire length | 38 m |
| Weight, net | 35.0 kg |
| Lifting speed | 11 |
| Lifting speed, layer 1 | 8,6 |
| Number of layers | 3 |
| FEM Group | 1Cm |
| Engine power | 1,1 |
| Standard | EN 14492-1 |