

HUCHEZ

## PRIMO Vinsch 500 kg, 3- fas

Art nr. 1PRIMO503BT

Electric winch 500 kg. Economical range subject to the same quality standard as the TRBoxter range.

Use:

- Simple lifting and pulling/hauling operations
- Intermediate operating factor
- Boat hauling
- Lifting doors, hatches
- Freight lifts
- Traps opening
- Theatre applications
- Swimming pool roofs

### Description

- Steel rigid structure.
- Mechanical welded steel drum with flanges allowing a secure fastening of the wire rope.
- Mechanical parts machined and protected by cataphoresis.
- Single phase 230 V motor brake with permanent capacitor - 50 Hz lifting type. P = 1.1 kW. Class F. IP 54 Protection.
- Low voltage control assuring user protection against electric risks.
- Up-down pendant control with emergency stop, cable 3 m long.
- Reducer in oil bath with helical gears.
- Limit switch as standard, very easy to adjust and extremely reliable.
- Options: rope-press roller and grooved drum.

### Specifications

Art nr.	1PRIMO503BT
Weight, net	35.0 kg
WLL	500 kg
Lifting speed, layer 1	8,6
Wire diameter	7 mm
Lifting speed	11
Engine power	1,1
Max wire length	38 m
Number of layers	3
FEM Group	1Cm
Standard	EN 14492-1