

Lifting Equipment



CHAIN HOISTS / LEVER HOISTS
BEAM TROLLEYS
BEAM CLAMPS
JACKS



SVERO

CHAIN HOIST & LEVER HOIST

SVERO

- Compact design according to standard EN 13157
- Powder-coated housing in steel provides good corrosion protection
- Safe, well protected, automatic load pressure brake
- Double ball-bearings on the load chain sprocket ensure perfect balance and smooth running
- Adapted lifting and/or operating height possible
- 0.5-20 tons can be obtained with overload protection
- Lever hoists with short handle, advantage in confined spaces
- QR code for easy access to manual
- Test- and CE-certificates and manual included



1414



1514

Chain Hoist	WLL kg	Lifting height (standard)	Load chain Ø mm	Min hook dim. mm	Falls	Weight kg
1411	250	3,0	4 X 12	280	1	6,4
1412	500	3,0	5 x 15	330	1	8,9
1414	1000	3,0	6,3 x 19	360	1	12,0
1416	2000	3,0	8 x 24	470	1	19,5
1417	3000	3,0	10 x 30	560	1	29,4
1419	5000	3,0	9 x 27	690	2	36,6
1423	10 000	3,0	10 x 30	810	3	64,1
1427	20 000	3,0	9 x 27	1060	8	182,0

Aluminium

1411AL	250	3,0	3,2 X 9	280	1	2,6
1412AL	500	3,0	4,3 x 12	330	1	5,0



1427

Lever Hoist	WLL kg	Lifting Height (standard)	Load chain Ø mm	Min Hook dim. mm	Falls	Weight kg
1511	250	1,0	4 x 12	235	1	2,2
1512	500	1,5	5 x 15	310	1	5,3
1513	800	1,5	5,6 x 17	340	1	7,0
1514	1000	1,5	6 x 18	340	1	8,0
1515	1500	1,5	7,1 x 21	400	1	11,1
1517	3000	1,5	10 x 28	520	1	20,5
1520	6000	1,5	10 x 28	640	2	29,5
1522	9000	1,5	10 x 28	690	3	49,0

Aluminium

1511AL	250	1,5	3,2 x 9	250	1	1,55
1512AL	500	1,5	4,3 x 12	250	1	2,55



1411AL/1511AL

BEAM TROLLEYS - standard / geared

SVERO

- Can be combined with most chain hoists, manual and electrical
- Standard trolleys fit on beams up to 300 mm
- Compact design, 3 parts alt. 5 parts for the larger models
- Powder-coated steel sides in stainless steel
- Ball bearing wheels in stainless steel
- Adjustable left/right threaded suspension bolt for easy assembly
- Geared trolleys with 3 m lifting height, adaption possible
- Test- and CE-certificates and manual included



20143A



21143A



20234



21274




Standard	WLL kg	Beam width mm	Min curve radius m	Weight kg
20123A	500	46-160	1,0	6,0
20124A	500	161-280	1,0	6,4
20133A	800	46-160	1,0	6,4
20143A	1000	50-160	1,25	9,4
20144A	1000	161-280	1,25	10,7
20153A	1600	50-160	1,25	9,4
20163A	2000	64-180	1,8	19,0
20164A	2000	181-300	1,8	21,0
20173A	3000	74-180	2,2	31,5
20174A	3000	181-300	2,2	34,0
20175A	3200	74-180	2,2	31,5
20193A	5000	82-180	2,5	55,0
20194A	5000	181-300	2,5	58,0
20203A	6300	82-180	2,5	55,0
20204A	6300	181-300	2,5	58,0
20213A	7000	82-180	2,5	55,0
20214A	7000	181-300	2,5	59,0
20234	10 000	220-300	3,0	95,0
3223A	10 000	220-300	3,5	120,0
Geared				
21123A	500	50-160	1,25	14,3
21124A	500	161-280	1,25	15,5
21143A	1000	50-160	1,25	14,3
21144A	1000	161-280	1,25	15,5
21163A	2000	64-180	1,8	25,3
21164A	2000	181-300	1,8	27,4
21173A	3000	74-180	2,2	38,2
21174A	3000	181-300	2,2	41,2
21193A	5000	82-180	2,5	56,7
21194A	5000	181-300	2,5	60,4
21234	10 000	220-300	3,0	98,0
21274	20 000	220-300	3,50	208,0
3423A	10 000	220-300	3,50	120,0

BEAM TROLLEYS

SVERO

- Can be combined with most chain hoists, manual and electrical
- Adapted for I- and H-beams
- Compact 3-piece construction
- Powder-coated steel or aluminium sides alt. stainless steel
- Ball bearing wheels
- Adjustable left/right threaded suspension bolt for easy assembly
- Alu trolley with square suspension bolt and locking adjustment pin
- Test- and CE-certificates and manual included

With Eye	WLL kg	Beam width mm	Min curve radius m	Weight kg
20123E	500	76-210	1,0	6,6
20143E	1000	85-215	1,25	10,3
20163E	2000	114-220	1,8	21,5
20173E	3000	127-253	2,2	33,0
20193E	5000	150-265	2,5	57,5
Stainless				
20123AS	500	46-160	1,0	6,3
20143AS	1000	50-160	1,25	10,0
20163AS	2000	64-180	1,8	21,2
20173AS	3000	74-180	2,2	32,0
Aluminium				
2312	500	80-180	1,25	4,9
2314	1000	80-180	1,25	5,1



BEAM TROLLEYS / BEAM STOP


- 2-wheeled models fits down to 300 mm turning radius
- Built-in suspension bolt as attachment point for hoists
- Stepless adjustable for beam width
- Easy assembling with handle
- Test- and CE-certificates and manual included

2-wheeled	WLL kg	Beam width mm	Min curve radius m	Weight kg
24123A	500	50-160	0,3	5,0
Adjustable				
25123A	500	70-200	1,0	8,0
25143A	1000	80-200	1,25	11,0
Beam Stop				
2830	10 000	90-300	–	2,3


BEAM TROLLEYS

SVERO

- Unique quick-lock for easy mounting without tools or loose parts
- Graduated suspension bolt for easy adjustment to the beam width
- Lightweight – lower weight than trolleys with the same capacity
- Compact 3-piece construction
- Powder-coated sides in stainless steel
- Ball bearing wheels in stainless steel
- QR code for easy access to manual
- Test- and CE-certificates and manual included




With quick-lock	WLL kg	Beam width mm	Min curve radius m	Weight kg
29123	500	80-160	0,9	3,5
29143	1000	80-160	1,0	5,5
29163	2000	80-160	1,25	10,7
29173	3000	80-160	1,8	16,1
29193	5000	100-180	2,2	25,6



BEAM CLAMPS

- Adjustable with locking for safe use
- Used as attachment point for chain- and electric hoists etc
- Low head room due to built-in suspension bolt
- Powder-coated steel
- Firm, secure grip on the lower flange, both vertically/horizontally
- Test- and CE-certificates and manual included



5014



5017

Model	WLL kg	Beam width mm	Weight kg
5014	1000	80-240	3,5
5016	2000	80-240	4,5
5017	3000	90-330	9,5
5019	5000	90-330	11,0
5023	10 000	90-350	16,0

BEAM TROLLEYS - Smart Hoist

- Trolley and chain hoist in aluminium
- Low weight and headroom
- Unique square suspension bolt and quick lock for easy assembly
- Non-sparking, fiberglass-reinforced and ball-bearing plastic wheels
- Can be ordered with adapted lifting height, 3 m standard
- Peli case as option
- Test- and CE-certificates and manual included

Model	WLL kg	Beam width mm	Min curve radius m	Weight kg
2212	500	110-180	1,25	10,1
2214	1000	110-180	1,25	11,3



2212

BEAM TROLLEYS - with integrated chain hoist

- Extremely low headroom
- Robust and sturdy design
- Lockable in parking mode (model 26)
- Integrated chain hoist
- Can be ordered with adapted lifting height, 3 m stand.
- Rubber shock absorbers
- Adjustable to different beam profiles
- Geared trolley (option model 27)
- Test- and CE-certificates and manual included



2614

Model	WLL kg	Beam width mm	Min curve radius m	Weight kg
2614	1000	74-150	2,5	69,0
2616	2000	82-156	4,0	118,0
2617	3200	103-223	4,5	181,0
2619	5000	119-215	6,0	293,0
2620	6300	119-215	6,0	296,0
2712	500	50-203	0,8	10,0
2714	1000	64-305	0,9	15,0



2712


JACKS - mechanical & hydraulic SVERO

- Lifting can be done on top and heel
- Mechanical: rack and pinion drive, folding of handle possible
- Railway: large base plate, handle with ratchet function
- Hydraulic: high precision, removable ratchet handle
- Test- and CE-certificates and manual included

Mechanical	WLL kg	Lifting height mm	Weight kg
1715	1500	70-900	3,5
1717	3000	70-1090	4,5
1719	5000	80-1075	9,5
1723	10 000	100-1190	11,0
1715RL	1500	70-900	3,5
1717RL	3000	70-1090	4,5
1719RL	5000	80-1075	9,5
1723RL	10 000	100-1190	11,0
Hydraulic			
1819	5000	25-573	25,0
1823	10 000	30-650	35,0
1825	25 000	58-720	109,0




OTHER SERVICES



Support



Education




Project solutions



Special adaptations



Service



Special solutions

For more information
about our products
svero.com



SVERO

Momarken 19
SE-556 50 Jönköping
SWEDEN
+46 36 316570
www.svero.com
info@svero.com